

Structural Transformations at the (001) Surface of Oxidized SrTiO₃ Studied by the X-ray Surface Diffraction

A. Kazimirov, M. J. Bedzyk (Northwestern U. and ANL), D.M. Goodner (Northwestern U.), J. Bai, and C.R. Hubbard (ORNL)

Abstract No. kazi1924

Beamline(s): X14A

Introduction: SrTiO₃ has gained recent attention as a high-*k* dielectric material with unique physical properties. Annealing in an oxygen atmosphere is typically used as a preparation step for producing well-ordered atomically clean SrTiO₃ surfaces [1]. Due to the complex defect chemistry and chemical instability this annealing is accompanied by stoichiometry changes in the near surface region and eventually leads to structural transformations [2]. We applied surface X-ray diffraction and CTR scattering to address these changes.

Methods and Materials: Single crystals of SrTiO₃(001) were annealed in an O₂ flow in a clean quartz tube at 900, 1000 and 1100°C for 3 hours. An AFM analysis showed the droplet-like features on the surfaces of all samples similar to those reported in [2].

The surface X-ray diffraction was performed at the X14A beamline. The incident X-ray beam was monochromized at 8.0 keV by the double-crystal monochromator, focused horizontally by a sagittally bent second mono-crystal and focused vertically by a mirror.

Results: Radial Q-scans measured from all oxidized SrTiO₃ samples at small grazing incident angle revealed a sequence of diffraction peaks (Fig.1). The circular ϕ -scans through these peaks showed weak intensity variations, i.e. the diffracted intensity is concentrated along quasi-powder rings. Such a diffraction pattern originates from the crystalline particles with nearly random in-plane orientation and was associated with the droplets observed by AFM. Analysis based on the available powder diffraction data [3] identified these crystallites as monoclinic TiO. Remarkable changes in specular (00L) CTR intensity were also found indicating significant structural modifications in SrTiO₃ surface layer.

Acknowledgments: Research sponsored by the Assistant Secretary for Energy Efficiency and Renewable Energy, Office of Transportation Technologies, as part of the High Temperature Materials Laboratory User Program, Oak Ridge National Laboratory, managed by UT-Battelle, LLC, for the U.S. Dept. of Energy under contract DE-AC05-00OR22725

References:

- [1] Q.D. Jiang, J. Zegenhagen, *Surface Science* **425** (1999) 343.
- [2] K. Szot, W. Speier, *Phys. Rev. B* **60** (1999) 5909.
- [3] Powder Diffraction File, International Center for Diffraction Data, Release 1999.




Figure 1. Radial Q-scan at some arbitrary azimuthal angle from the SrTiO₃(001) surface oxidized at 1100°C. The incident angle is 0.62 deg. The Q-axis is in reciprocal lattice units for SrTiO₃ (a=3.905 Å). Each of the quasi-powder peaks is labeled according to the corresponding d-spacing in Å.